

# Junior Phenolic Folding Shower Seats

## JR. Rectangle

Configuration:  
**63 Series**  
Phenolic

### Application Use:



### Specifications

Folding shower seat manufactured by ELCOMA from 1" (25mm) diameter, 18 gauge and 1.25" x 1.25" (32mm x 32mm), 16 gauge, type 304 stainless steel tubing with #4 satin finish. Wall mount brackets shall be 12 gauge type 304 stainless steel. Solid Phenolic seat shall be 1/2" (13mm) thick and shall be fire and mildew resistant. Shower Seat shall comply with all applicable federal, provincial and local building and safety codes.

White shown, Also available in Woodgrain



### Custom sizes are available to suit special requirements.

16" x 16"	(406mm x 406mm)	White	Model # 63-PH1451601
16" x 16"	(406mm x 406mm)	Woodgrain	Model # 63-PH1451615
18" x 16"	(457mm x 406mm)	White	Model # 63-PH1451801
18" x 16"	(457mm x 406mm)	Woodgrain	Model # 63-PH1451815

Elcoma Shower Seats have been designed and tested to withstand 400lbs. (182kgs) of load when properly installed.\* This exceeds HUD, FHA, VA, ADA, ANSI and other federal, provincial, and local codes. \*Shower seats can only be as strong as what they are mounted to. It is imperative when installing any shower seat to consult with a qualified contractor to insure you have sufficient backing.

